



# Technical Specifications

	SURE CODE™ 65	SURE CODE™ 68	SURE CODE™ 68P	SURE CODE™ 72
General Description	Workhorse, prints up to 2 lines at speeds up to 1230 f/m	All advantages of the 65, plus prints up to 5 lines	Uniquely designed to handle high durability pigmented inks	High speed up to 5 lines of text at speeds up to 1624 f/m
Line Speed	1230 f/m (375 m/m) 6.25 m/sec.	1230 f/m (375 m/m) 6.25 m/sec.	1230 f/m (375 m/m) 6.25 m/sec.	1624 f/m (495 m/m) 8.25m/sec.
Lines of Print	2	1-4 lines, optional 5	1-4 lines, optional 5	1-4 lines, optional 5
Character Height	0.06" to 0.31" 1.4mm to 8mm	0.06" to 0.47" 1.4mm to 12mm	0.06" to 0.47" 1.4mm to 12mm	0.05" to 0.35" 1.2mm to 9mm
Font Height	16 dots	32 dots	32 dots	32 dots
Message Memory	100	1000	1000	1000
User Interface 1	High contrast LCD touch Screen (blue, red, green, yellow)	High contrast LCD touch Screen (blue, red, green, yellow)	High contrast LCD touch Screen (blue, red, green, yellow)	High contrast LCD touch Screen (blue, red, green, yellow)
User Interface 2	Keyboard	Keyboard	Keyboard	Keyboard
USB, RS232	Yes	Yes	Yes	Yes
RS485, Ethernet	No	Optional	Optional	Optional
iModule™ Service Life*	18 months (4,000 hours)	18 months (6,000 hours)	12 months (2,100 hours)	18 months (8,000 hours)
Enclosure	Stainless steel	Stainless steel	Stainless steel	Stainless steel
Nozzle Diameter	60µm	60µm, optional 50µm	60µm	50µm
Dimensions	18" H x 11.8"W x 8.3"D 457mm x 300mm x 211mm	18" H x 11.8"W x 8.3"D 457mm x 300mm x 211mm	18" H x 11.8"W x 8.3"D 457mm x 300mm x 211mm	18" H x 11.8"W x 8.3"D 457mm x 300mm x 211mm
Weight	28.7lbs 13 kg	28.7lbs 13 kg	28.7lbs 13 kg	28.7lbs 13 kg
Power Supply	120v, 60hz	120v, 60hz	120v, 60hz	120v, 60hz
Power Consumption	< 30W	< 30W	< 30W	< 30W
Power cable length	9.8ft 3m	9.8ft 3m, Optional 4m, 6m	9.8ft 3m, Optional 4m, 6m	9.8ft 3m, Optional 4m, 6m
Ink Type	Dye	Dye	Pigment	Dye
Fluid Cartridge Volume	30 oz 900 ml	30 oz 900 ml	24 oz / 700 ml ink, 30 oz / 900 ml solvent	30 oz 900 ml
Warranty	24 months	24 months	24 months	24 months

### Optional Accessories

Photo Eye Kit, Alert Light, Shaft Encoder, Relay Stop Kit, Sure Code™ Printer stand, Sure Code™ Printhead Stand

\* iModule™ is upgradeable to 6000 or 8000 hours.

### Font & Symbol Samples



### Printer & Printhead Dimensions

